

Wall brackets

Aluminium L-brackets

Available with back perforation for all common anchoring surfaces.
Alloy EN AW-6063 T66.

- | | | |
|--|---|---|
| <ul style="list-style-type: none"> • Back (W) 40 resp. 43 mm • Reach (A) 40-320 mm • Material thickness (M) 3 mm + 4 mm • Height 85 mm (H) | <ul style="list-style-type: none"> • Back (W) 40 resp. 43 mm • Reach (A) 40-320 mm • Material thickness (M) 3 mm + 4 mm • Height 160 mm (H) | <ul style="list-style-type: none"> • Back (W) 40 resp. 43 mm • Reach (A) 40-320 mm • Material thickness (M) 3 mm + 4 mm • Height 250 mm (H) |
|--|---|---|


| | W/A/M-H | W/A/M-H | W/A/M-H |
|--------|---------------|----------------|----------------|
| WB 0 | 40/40/3-85 | 40/40/3-160 | 40/40/3-250 |
| WB 1 | 40/60/3-85 | 40/60/3-160 | 40/60/3-250 |
| WB 2 | 40/80/3-85 | 40/80/3-160 | 40/80/3-250 |
| WB 3 | 40/100/3-85 | 40/100/3-160 | 40/100/3-250 |
| WB 4 | 40/120/3-85 | 40/120/3-160 | 40/120/3-250 |
| WB 5 | 40/140/3-85 | 40/140/3-160 | 40/140/3-250 |
| WB 6 | 40/160/3-85 | 40/160/3-160 | 40/160/3-250 |
| WB 7 | 40/180/4/3-85 | 40/180/4/3-160 | 40/180/4/3-250 |
| WB 8 | 40/200/4/3-85 | 40/200/4/3-160 | 40/200/4/3-250 |
| WB 8,5 | 40/210/4/3-85 | 40/210/4/3-160 | 40/210/4/3-250 |
| WB 9 | 40/220/4/3-85 | 40/220/4/3-160 | 40/220/4/3-250 |
| WB 9,5 | 40/230/4/3-85 | 40/230/4/3-160 | 40/230/4/3-250 |
| WB 10 | 43/240/4/3-85 | 43/240/4/3-160 | 43/240/4/3-250 |
| WB 11 | 43/260/4/3-85 | 43/260/4/3-160 | 43/260/4/3-250 |
| WB 12 | 43/280/4/3-85 | 43/280/4/3-160 | 43/280/4/3-250 |
| WB 13 | 43/300/4/3-85 | 43/300/4/3-160 | 43/300/4/3-250 |
| WB 14 | 43/320/4/3-85 | 43/320/4/3-160 | 43/320/4/3-250 |

Aluminium U-brackets

Available with back perforation for all common anchoring surfaces.
Alloy EN AW-6063 T66.

- | | |
|---|--|
| <ul style="list-style-type: none"> • Reach (A) 40-180* mm • Back (W) 55 resp. 57 mm • Height (H) 70 mm • Material thickness (M) in mm a/b/a | <ul style="list-style-type: none"> • Reach (A) 40-180* mm • Back (W) 55 resp. 57 mm • Height (H) 160 mm • Material thickness (M) in mm a/b/a |
|---|--|

M = a/b/a



| | A/W/A-H | a/b/a | A/W/A-H |
|---------|---------------|---------|----------------|
| AUH 0 | 40/55/40-70 | 2/3,5/2 | 40/55/40-160 |
| AUH 1 | 60/55/60-70 | 2/5/2 | 60/55/60-160 |
| AUH 2 | 80/55/80-70 | 2/5/2 | 80/55/80-160 |
| AUH 3 | 100/55/100-70 | 2/5/2 | 100/55/100-160 |
| AUH 4 | 120/55/120-70 | 2/5/2 | 120/55/120-160 |
| AUH 4,5 | 135/57/135-70 | 3/5/3 | 135/57/135-160 |
| AUH 5,5 | 150/57/150-70 | 3/5/3 | 150/57/150-160 |
| AUH 7 | 180/57/180-70 | 3/5/3 | 180/57/180-160 |

* larger protrusions available on request

Aluminium bracket extensions

Maximum extension of the protrusion: length minus 24 mm overlap area.
Alloy EN AW-6063 T66.

- | | |
|--|---|
| <ul style="list-style-type: none"> • Length (L) 60-200 mm • Height (H) 85 mm | <ul style="list-style-type: none"> • Length (L) 60-200 mm • Height (H) 160 mm |
|--|---|

| | L-H | L-H |
|-------|--------|---------|
| WBV 1 | 60-85 | 60-160 |
| WBV 2 | 80-85 | 80-160 |
| WBV 3 | 100-85 | 100-160 |
| WBV 4 | 120-85 | 120-160 |
| WBV 5 | 140-85 | 140-160 |
| WBV 6 | 160-85 | 160-160 |
| WBV 7 | 180-85 | 180-160 |
| WBV 8 | 200-85 | 200-160 |

Aluminium T-brackets

Available with back perforation for all common anchoring surfaces.
Alloy EN AW-6063 T66.

- | | |
|---|--|
| <ul style="list-style-type: none"> • Back (W) 120 mm • Reach (A) 220-380 mm • Height (H) 85 mm • Material thickness (M) in mm a/b/a | <ul style="list-style-type: none"> • Back (W) 120 mm • Reach (A) 220-380 mm • Height (H) 160 mm • Material thickness (M) in mm a/b/a |
|---|--|

M = a/b/a



6 mm/4.5 - 10.5 mm/6 mm
Material thickness b decreases with increasing reach.

| | W/A-H | W/A-H |
|--------|------------|-------------|
| WBT 9 | 120/220-85 | 120/220-160 |
| WBT 10 | 120/240-85 | 120/240-160 |
| WBT 11 | 120/260-85 | 120/260-160 |
| WBT 12 | 120/280-85 | 120/280-160 |
| WBT 13 | 120/300-85 | 120/300-160 |
| WBT 14 | 120/320-85 | 120/320-160 |
| WBT 15 | 120/340-85 | 120/340-160 |
| WBT 16 | 120/360-85 | 120/360-160 |
| WBT 17 | 120/380-85 | 120/380-160 |

Stainless steel L-brackets

With back perforation 10.5 x 15 mm or 6.6 x 15 mm.
Material EN 1.4162

| | W/A/M-H | W/A/M-H |
|-------|---|--|
| | <ul style="list-style-type: none"> • Wall back (W) 43 mm • Protrusion (A) 120-400 mm • Material thickness (M) 1.7 mm • Height (H) 70 mm | <ul style="list-style-type: none"> • Wall back (W) 43 mm • Protrusion (A) 120-400 mm • Material thickness (M) 1.7 mm • Height (H) 150 mm |
| EH 4 | 43/120/1.7-70 | 43/120/1.7-150 |
| EH 5 | 43/140/1.7-70 | 43/140/1.7-150 |
| EH 6 | 43/160/1.7-70 | 43/160/1.7-150 |
| EH 7 | 43/180/1.7-70 | 43/180/1.7-150 |
| EH 8 | 43/200/1.7-70 | 43/200/1.7-150 |
| EH 9 | 43/220/1.7-70 | 43/220/1.7-150 |
| EH 10 | 43/240/1.7-70 | 43/240/1.7-150 |
| EH 11 | 43/260/1.7-70 | 43/260/1.7-150 |
| EH 12 | 43/280/1.7-70 | 43/280/1.7-150 |
| EH 13 | 43/300/1.7-70 | 43/300/1.7-150 |
| EH 14 | 43/320/1.7-70 | 43/320/1.7-150 |
| EH 15 | 43/340/1.7-70 | 43/340/1.7-150 |
| EH 16 | 43/360/1.7-70 | 43/360/1.7-150 |
| EH 17 | 43/380/1.7-70 | 43/380/1.7-150 |
| EH 18 | 43/400/1.7-70 | 43/400/1.7-150 |

Stainless steel U-brackets

With back perforation 10.5 x 15 mm or 6.6 x 15 mm.
Material EN 1.4404

| | A/W/A-H | A/W/A-H |
|--------|--|---|
| | <ul style="list-style-type: none"> • Protrusion (A) 60-300 mm • Wall back (W) 56 mm • Height (H) 70 mm • Material thickness (M) 2.5 mm | <ul style="list-style-type: none"> • Protrusion (A) 60-300 mm • Wall back (W) 56 mm • Height (H) 150 mm • Material thickness (M) 2.5 mm |
| EUH 1 | 60/56/60-70 | 60/56/60-150 |
| EUH 2 | 80/56/80-70 | 80/56/80-150 |
| EUH 3 | 100/56/100-70 | 100/56/100-150 |
| EUH 4 | 120/56/120-70 | 120/56/120-150 |
| EUH 5 | 140/56/140-70 | 140/56/140-150 |
| EUH 6 | 160/56/160-70 | 160/56/160-150 |
| EUH 7 | 180/56/180-70 | 180/56/180-150 |
| EUH 8 | 200/56/200-70 | 200/56/200-150 |
| EUH 9 | 220/56/220-70 | 220/56/200-150 |
| EUH 10 | 240/56/240-70 | 240/56/240-150 |
| EUH 11 | 260/56/260-70 | 260/56/260-150 |
| EUH 12 | 280/56/280-70 | 280/56/280-150 |
| EUH 13 | 300/56/300-70 | 300/56/300-150 |